

Auslegungstabelle für *FeRo* – Plattenwärmeübertrager in gelöteter Ausführung für Systemtrennungen

Leistung ¹⁾ °C Seite 1	Typ	BHM 22 – 10	BHM 22 – 20	BMH 22 – 30	BHM 22 – 40	BHM 22 – 50	BHM 24 – 30	BHM 24 – 40
	°C Seite 2							
90 / 70	45 / 55	10	18	24	29	32	38	46
	40 / 50	10	18	24	29	32	38	46
	35 / 45	10	18	24	29	32	38	46
	30 / 40	10	18	24	29	32	38	46
80 / 60	45 / 55	10	18	24	29	32	38	46
	40 / 50	10	18	24	29	32	38	46
	35 / 45	10	18	24	29	32	38	46
	30 / 40	10	18	24	29	32	38	46
70 / 50	45 / 55	-	10	16	21	27	38	46
	40 / 50	10	18	24	29	32	38	46
	35 / 45	10	18	24	29	32	38	46
	30 / 40	10	18	24	29	32	38	46
60 / 50	40 / 50	8	17	23	28	31	35	44
	35 / 45	8	17	23	28	31	35	44
	30 / 40	8	17	23	28	31	35	44
55 / 45	35 / 45	8	17	23	28	31	35	44
	30 / 40	8	17	23	28	31	35	44

¹⁾ Leistung in kW, Druckverlust max. 15 kPa